
RD-3 Rotary Drive

Barringtor

0-180° Fully Adjustable

Features


- Angle of rotation adjusted with built in stop screws with fine threads
- Stop screws are compatible with sensing switches
- End stops deceleration with available cushions
- Designed for production rates and long life
- Piston has hardened pin to strike for longevity
- Two sealed ball bearings at top and bottom of drive shaft
- Tapped holes and offset dowel pin area in shaft and driving flange allows higher torque transmittal and accuracy
- Bearings are positioned very close to the drive



gear for rigidity, precision, wear resistance and accuracy.

Shaft is stopped with an adjustable hard stopscrew against a hardened pin, eliminating backlash

Dimensions



RD-3 Rotary Drive



Technical Data

Bore = 1.25" Repeat accuracy = +/-0.0005"

Life expectancy = 5-6 million cycles Compressed air = 60 to 100 psi Angle of rotation = 0 to 180 degrees


Weight = 5 lbs Air connection = 10-32

Max radial

bearing load = 20 lbs

Max axial


bearing load = 36 lbs



Pressure	Piston Area (in^2)	Max Torque (in-lbs)
60	1.227	33
70	1.227	38
80	1.227	44
90	1.227	49
100	1.227	55

The diagrams above depict the load (F) on an arm of length = y. Also shown is the torque of the RD-3 which is given in the chart:

Load vs. Distance for Different Cycle Times (@80psi) Load (for any P) = Graph value *(P/80)



Options

Sensing switches are available as an option. They are mounted to the stopscrews as seen in the photo to the right. For specifications on sensing please see page 49. Shocks or cushions are also available.

